

# ARAL SuperTronic G 0W-40

Synthetic technology engine oil for gasoline or diesel engines



## Description

Synthetic technology high-performance engine oil for passenger cars:

- For gasoline or diesel engines
- Provides an outstanding anti wear performance
- High performance motor oil – designed for longest drain intervals at flexible maintenance periods
- Provides less fuel and oil consumption

## Application

ARAL SuperTronic G 0W-40 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an ACEA A3/B4, API SP or earlier specification 0W-40 lubricant.

ARAL SuperTronic G 0W-40 is approved for use in vehicles from leading manufacturers, please refer to the specifications section and your owners handbook.

## Typical Characteristics

Name	Method	Units	ARAL SuperTronic G 0W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.844
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	13.3
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	76
Viscosity Index	ASTM D2270	None	180
Viscosity, CCS -35C (0W)	ASTM D5293	mPa.s (cP)	5980
Pour Point	ASTM D97	°C	-45
Flash Point, PMCC	ASTM D93	°C	210
Ash, Sulphated	ASTM D874	% wt	1.2

## Product Performance Claims

ACEA A3/B4  
API SP  
BMW Longlife-01  
MB-Approval 229.5  
Porsche A40  
Renault RN0700 / RN0710  
VW 502 00/ 505 00  
Fulfills the technical requirements of MB 229.3

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

ARAL SuperTronic G 0W-40

03 Nov 2023

Aral, the Aral logo and related marks are trademarks of Aral Aktiengesellschaft, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Aral Aktiengesellschaft, Geschäftsbereich Schmierstoffe, Überseeallee 1, D-20457 Hamburg

01801-11 55 11

[www.aral-lubricants.de](http://www.aral-lubricants.de)